

# SUN-FLOW SF-50



Code: SF-50

P.V.C. 150 PSI RANGE

**BRICK RED DISCHARGE HOSE**

NOMINAL SIZE	I.D.	APPROX WALL	Max. W.P. at 70°F psi	DESIGN B.P. psi	U.S.A	JAPAN
					APPROX. Wt. 300ft	APPROX. Wt. 300ft
1-1/2"	1.61"	0.079"	150	450	80 lbs	64 lbs
2"	2.09"	0.087"	150	450	103 lbs	85 lbs
2-1/2"	2.56"	0.091"	150	450		119 lbs
3"	3.07"	0.095"	150	450	164 lbs	158 lbs
4"	4.13"	0.102"	150	450	254 lbs	225 lbs
6"	6.18"	0.119"	150	450	400 lbs	375 lbs
8"	8.19"	0.134"	115	350		566 lbs

- **STND. LENGTH:** 300 ft. per bale (Special order for longer lengths)
- **TEMP. RANGE:** -5°F to 170°F
- **APPLICATIONS:** Mines, Construction, etc.
- **CONSTRUCTION:** 3-Ply Polyester Yarns. Both tube and cover are extruded simultaneously to obtain maximum bonding.
- **FLAME RESISTANT:** **USMSHA IC-150/1** (Size 1-1/2", 2", 2-1/2") **Special order only**
- **CAUTION:** For liability purposes, if temperature exceeds 110°F the working pressure will go down. Please check with factory to ensure sufficient safety factor.