

SUN-FLOW SF-55



Code: SF-55 GRAY

RECOMMENDED FOR **SPRINKLER, PIVOT AND WATER TRANSPORT** - THIS HOSE HAS LESS DIAMETER GROWTH AND ELONGATION THEREFORE ALLOWING FOR MUCH GREATER EASE OF RE-COUPLING AFTER USE.

NOMINAL SIZE	I. D.	APPROX. WALL	MAX. W.P. at 70°F psi	APPROX. Wt. 300ft
1-1/2"	1.61"	0.063"	150	60 lbs
2"	2.08"	0.087"	150	108 lbs
3"	3.07"	0.100"	150	194 lbs
4"	4.13"	0.114"	100	280 lbs
(120mm) 5"	5.07"	0.130"	100	400 lbs
6"	6.10"	0.146"	100	500 lbs

■ TOUGH HEAVY DUTY APPLICATIONS:

Sprinkler, Pivot & Traveler, Water Transportation.
(Pivot & Traveler use 3", 4", 5", 6" only)

■ TEMP. RANGE:

-5°F to 170°F

■ CONSTRUCTION:

3-Ply Polyester Yarns. Both tube and cover are extruded simultaneously to obtain maximum bonding.

■ CAUTION:

For liability purposes, if temperature exceeds 110°F the working pressure will go down. Please check with factory to ensure sufficient safety factor.